

TW 5204 FD



Feature:

- Support ONVIF; access third party;
- information pushed to your phone and other functions;
- Support web, VMS, center platform management software CMS
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVi/AHD/TVI/CVI/CVBS/IP six signals;
- Support intelligent analysis: Human detection, face detection

Specification

Model	TW 5204 FD
--------------	------------

Interface

Preview	1/4/6
----------------	-------

Video / Audio

Codec	H.265
Monitor quality	VGA(1080P at most);HDMI(1080P at most);CVBS
Preview ability	4*5M-N@20fps (6 in 1) /4*4M-N@30fps (6 in 1) /4*1080P (6 in 1) default:5M-N
Encode ability	4*5M-N@20fps (6 in 1) /4*4M-N@30fps (6 in 1) /4*1080P (6 in 1) default:5M-N
Decode ability	4*5M-N@20fps (6 in 1) /4*4M-N@30fps (6 in 1) /4*1080P (6 in 1) default:5M-N
Multi-mode input	4*5M-Analog: 4*5M-N hybrid: 4*5M-N (analog) +2*1080P (network) network: 16*1080P; 16*5MN@20fps (6 in 1) /4*4M-N@30fps (6 in 1) /4*1080P (6 in 1) default:5M-N
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio compression	G.711A

Audio Record & playback

Record mode	manual>alarm>motion detection>timing
Local Playback	2ch(analog input mode)
Search mode	Search by time, calendar, event, channel e Face
Video storage	HDD, network
Backup mode	Network, USB
Video input	4ch BNC
Video output	1ch VGA, 1ch HDMI, 1ch BNC
Audio I/O	4/1
PTZ control	Support kinds of PTZ protocols
USB	2* USB 2.0 ports
HDD	1*SATA ports (Support up to 1 SATA interfaces Maximum support 8TB) *For HD use over 2TB, replace the 2A DVR source with a higher power source (12V – 5A Not Included)*

Network

Network interface	RJ45 10M/100M self-adaption
--------------------------	-----------------------------

General

Power supply	12V/2A
Power Consumption	<15W (without HDD)
Working environment	Temperature:0°C—+55°C · Humidity:10%—90%, Atm:86kpa—106kpa
Dimension	245mm*210mm*45mm
Weight	796g