

## TW 6208 FD



### Feature:

- Support ONVIF; access third party
- Support web, VMS, center platform management software CMS
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals
- Support intelligent analysis: Human detection, face detection

## Specification

Model	TW 6208 FD
-------	------------

### Interface

Preview	1/4/9/10
---------	----------

### Video / Audio

Codec	H.265
Monitor quality	VGA(1080P at most);HDMI(2K at most);CVBS
Preview ability	8*1080N (6 in 1) / 4*5M-N (6 in 1)
Encode ability	8*1080N@15 fps(6 in 1) / 4*5M-N@25fps(6 in 1)
Decode ability	8*1080N@15 fps(6 in 1)/4*5M-N@25fps(6 in 1)
Multi-mode input	Analog: 8*1080N; 4*5M-N hybrid: 8*1080N (analog) +2*1080P (network) Network: 16*1080P; 16*5M
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set
Audio compression	G.711A

### Audio Record & playback

Record mode	manual>alarm>motion detection>timing
Local Playback	4ch(analog input mode)
Search mode	Search by time, calendar, event, channel
Video storage	HDD, network
Backup mode	Network, USB
Video input	8ch BNC
Video output	1ch VGA, 1ch HDMI, 1ch CVBS
Audio I/O	4/1
PTZ control	Support kinds of PTZ protocols
USB	2* USB 2.0 ports
HDD	1*SATA ports (Support up to 1 SATA interfaces Maximum support 8TB) *For HD use over 2TB, replace the 2A DVR source with a higher power source (12V – 5A Not Included)*

## Network

Network interface	RJ45 10M/100M self-adaption
-------------------	-----------------------------

## General

Power supply	12V/2A
Power Consumption	<15W (without HDD)
Working environment	Temperature:0°C—+55°C · Humidity:10%—90%, Atm:86kpa—106kpa
Dimension	245mm*210mm*45mm
Weight	960g