

### TW 6216 FD

- Feature:
  -Support H. 265
  -Support VGA, HDMI full HD output simultaneously;Support CVBS output
  -Support ONVIF; access third party;
  -Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
  -Support web, VMS, center platform management software CMS
  -Support various mobile monitoring (iPhone, Android);
  -Remote Access, With DNS (ARSP),easy to monitor remotely
  -Support UTC, control signal& video stream transmit through one single coaxial
  -Support XVI/AHD/TVI/CVI/CVBS/IP six signals;
  -Support intelligent analysis: Human detection, face detection

# **Specification**

TW 6216 FD Model

#### Interface

**Preview** 1/4/8/9/16

#### Video / Audio

| Codec                   | H.265  |
|-------------------------|--|
| Monitor quality         | VGA (1080P at most); HDMI ;CVBS  |
| Preview ability         | 16*1080N(6 in 1)   |
| Encode ability          | 16*1080N@15fps(6 in 1)   |
| Decode ability          | 16*1080N@15fps(6 in 1)   |
| Multi-mode input        | Analog : 16*1080N<br>hybrid : 16*1080N ( analog ) + 4*1080P ( network )<br>network : 16*1080P - 8*5M |
| <b>Motion Detection</b> | Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set          |
| Audio compression       | G.711A   |
| Intercom                | support  |

# Audio Record & playback

| Record mode    | manual>alarm>motion detection>timing  |
|----------------|---|
| Local Playback | 16ch(analog input mode)   |
| Search mode    | Search by time, calendar, event, channel  |
| Video storage  | HDD, network  |
| Backup mode    | Network, USB  |
| Video input    | 16ch BNC  |
| Video output   | 1ch HDMI/ 1ch VGA/ 1ch CVBS   |
| Audio I/O      | 2 (Can be extended to 6ch) /1   |
| PTZ control    | 1*RS485, Support kinds of PTZ protocols   |
| USB            | 2* USB 2.0 ports  |
| HDD            | 1*SATA ports (Support up to 1 SATA interfaces,Maximum support 8T) *For HD use over 2TB, replace the 2A DVR source with a higher power source (12V – 5A* Not Included) |

### Network

| Network interface | RJ45 10M/100M self-adaption |
|-------------------|-----------------------------|
|-------------------|-----------------------------|

# General

| Power supply        | 12V/2A  |
|---------------------|---|
| Power Consumption   | <15W (without HDD)  |
| Working environment | Temperature:0°C−+55°C · Humidity:10%−90% · Atm:86kpa−106kpa |
| Dimension           | 245mm*210mm*45mm  |
| Weight              | 960g  |





