



TW-2156 POE STAR PLUS

3MP H.265 NETWORK WARMLIGHT FULL COLOR IR BULLET CAMERA

1/2.7" Progressive Scan CMOS Video Compression: H.265 / H.264
Support dual stream Effective Pixels: 2304(H)*1296(V) Minimum
Illumination: Full Color: 0.01Lux@F1.2 2pcs warmlight array LEDs,
IR distance: 20-25m 3.6mm 3MP Board Lens Support 2D/3D Noise
Reduction and Digital WDR Power supply: DC12V/PoE (IEEE802.3af)

Specification

Model	TW-2156 POE STAR PLUS
Image Sensor	1/2.7" Progressive Scan CMOS
Picture Pixels	2304(H)*1296(V)
Scanning System	Progressive scanning
Min. Illumination	Full Color: <u>0.01Lux@F1.2</u>
Shutter Speed	1/50 (1/60) s-1/10,000 s
Day and Night	650 Filter, Full Color
Wide Dynamic Range	Digital WDR, >80dB
S/N Ratio	>50dB (AGC OFF)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	2D / 3D NR

Lens

Focal Length	3.6mm 3MP Board Lens
---------------------	----------------------

Infrared

IR LED No.	2pcs warmlight array LEDs
IR Distance	20m

Video

Video Compression	H.265 / H.264
Streaming Capability	Dual stream
Image Resolution	Main stream: 3MP (2304*1296) / 2MP (1920*1080) / 1MP (1280*720) Sub stream: 448P (800*448) / D1 (704*576) / 360P (640*360) / CIF (352*288)
Video Frame Rate	3MP@30fps
Video Bit Rate	0.1M ~ 8Mbps

Network

Ethernet	RJ-45 (10/100Base-T)
Network Protocols	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS
System Compatibility	ONVIF 2.4
Smart Phone	iPhone, iPad, Android Phone

General

Operating Temperature	-20°C-60°C
Operating Humidity	Less than 95%RH (No condensation)
Power Supply	DC12V/PoE (IEEE802.3af)
Housing	IP66-rated white color metal case + plastic cover, with 3-axis cable- managed Bracket
Dimensions	62*67*180mm