



TWG-2220 POE

- *7 Inch, half metal body construction, IP66
- *HD-IP PTZ medium speed dome with OSD
- *6PCS IR LED+2PCS Laser LED: IR distance 150 meters
- *Support P2P function, ONVIF, H.264/H.265/MJPEG
- *Wall mount bracket, DC12V power supply
- *POE is optional

Specification

MODEL	TWG-2220 POE
Camera	
Output pixel	2MP 1920*1080
Lens	22X f=4.7mm~96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTC P, NTP
Software Control	IE, IPC ModuleTool, IVS365
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Rotation Speed	Pan: 0~80°/s , Tilt:0~40°/s
Auto Flip	Support
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmabel(scan speed 1-64 levels setting available)
Guard Tours	3 groups(Max.16 points, dwell time user selectable)

Operating temperature	-40°~+60°C
Operation menu	English
Power	DC 12V
Consumption	≤15W
Related validation	Ip66
IR distance	Up to 100 meters
LEDs	6PCS IR LED+2PCS Laser LED