



Fazendo parte da sua vida



MODEL	TW-2256 POE DUAL LIGHT
Camera	
Image Sensor	1/2.7" Progressive Scan CMOS
Picture Pixels	2560(H)*1440(V) 4MP
Scanning System	Progressive scanning
Min. Illumination	Dual Light : 0.01Lux@F1.2
Shutter Speed	1/50 (1/60) s-1/10,000 s
Day and Night	650 Filter, Dual Light
Wide Dynamic Range	Digital WDR, >80dB
S/N Ratio	>50dB (AGC OFF)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	2D / 3D NR
Lens	
Focal Length	3.6mm 4MP Board Lens
Infrared	
IR LED No.	2pcs warmlight array LEDs / IR
IR Distance	20-25m
Video	
Video Compression	H.265 / H.264
Streaming Capability	Dual stream
Image Resolution	Main stream: 4MP (2560*1440) 3MP (2304*1296) / 2MP (1920*1080) / 1MP (1280*720) Sub stream: 448P (800*448) / D1 (704*576) / 360P (640*360) / CIF (352*288)
Video Frame Rate	4MP@30fps
Video Bit Rate	0.1M ~ 8Mbps
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Protocols	RTMP, ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS
System Compatibility	ONVIF 2.4
Smart Phone	iPhone, iPad, Android Phone
General	
Operating Temperature	-20°C-60°C
Operating Humidity	Less than 95%RH (No condensation)
Power Supply	DC12V/PoE (IEEE802.3af)
Housing	IP66-rated white color metal case + plastic cover, with 3-axis cable- managed Bracket
Dimensions	62*67*180mm