



TW-3360 POE

### **3MP H.265 NETWORK FISHEYE IR DOME CAMERA**

1/2.7" Progressive Scan CMOS Video Compression: H.265 / H.264 Support dual stream  
 Effective Pixels: 2304(H)\*1296(V) Minimum Illumination: Color: 0.01Lux@F1.2, B/W: 0.001  
 Lux@F1.2, 0Lux (IR ON) 3pcs array LEDs, IR distance: 20m  
 1.7mm Fisheye IR Lens Support 2D/3D Noise Reduction and Digital  
 WDR Power supply: DC12V/PoE (IEEE802.3af)

## **Specification**

<b>MODEL</b>	TW-3360 POE
<b>Camera</b>	
<b>Image Sensor</b>	1/2.7" Progressive Scan CMOS
<b>Picture Pixels</b>	2304(H)*1296(V)
<b>Scanning System</b>	Progressive scanning
<b>Min. Illumination</b>	Color: 0.01Lux@F1.2, B/W: 0.001Lux@F1.2, 0Lux
<b>Shutter Speed</b>	1/50 (1/60) s-1/10,000 s
<b>Day and Night</b>	Auto (ICR) / Color / B/W
<b>Wide Dynamic Range</b>	Digital WDR, >80dB
<b>S/N Ratio</b>	>50dB (AGC OFF)
<b>White Balance</b>	Auto / Manual
<b>Gain Control</b>	Auto / Manual
<b>Noise Reduction</b>	2D / 3D NR
<b>Lens</b>	
<b>Focal Length</b>	1.7mm Fisheye IR Lens
<b>Infrared</b>	
<b>IR LED No.</b>	3pcs array LEDs
<b>IR Distance</b>	20-m

## Video

<b>Video Compression</b>	H.265 / H.264
<b>Streaming Capability</b>	Dual stream
<b>Image Resolution</b>	Main stream: 3MP (2304*1296) / 2MP (1920*1080) / 1MP (1280*720) Sub stream: 448P (800*448) / D1 (704*576) / 360P (640*360) / CIF (352*288)
<b>Video Frame Rate</b>	3MP@30fps
<b>Video Bit Rate</b>	0.1M ~ 8Mbps

## Network

<b>Ethernet</b>	RJ-45 (10/100Base-T)
<b>Network Protocols</b>	ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS
<b>System Compatibility</b>	Supports Onvif 2.4 Protocol
<b>Smart Phone</b>	iPhone, iPad, Android Phone

## General

<b>Operating Temperature</b>	-20°C-60°C
<b>Operating Humidity</b>	Less than 95%RH (No condensation)
<b>Power Supply</b>	DC12V/PoE (IEEE802.3af)
<b>Housing</b>	White color metal case, with Bracket
<b>Dimensions</b>	φ121*85mm