



Fazendo parte da sua vida

Model: TW-3380 FY POE



Brief Description:

3MP H.265 NETWORK FISHEYE IR BULLET CAMERA

Features

1/2.7" Progressive Scan CMOS Video

Compression: H.265 / H.264

Support dual stream

Effective Pixels: 2304(H)*1296(V)

Minimum Illumination: Color: 0.01Lux@F1.2, B/W: 0.001Lux@F1.2, 0Lux (IR ON)

30pcs array LEDs, IR distance: 20m

1.7mm Fisheye IR Lens

Support 2D/3D Noise Reduction and Digital WDR

Power supply: DC12V/PoE (IEEE802.3af)

| MODEL | TW-3380 FY POE |
|-----------------------|--|
| Camera | |
| Image Sensor | 1/2.7" Progressive Scan CMOS |
| Picture Pixels | 2304(H)*1296(V) |
| Scanning System | Progressive scanning |
| Min. Illumination | Color: 0.01Lux@F1.2, B/W: 0.001Lux@F1.2, 0Lux |
| Shutter Speed | 1/50 (1/60) s-1/10,000 s |
| Day and Night | Auto (ICR) / Color / B/W |
| Wide Dynamic Range | Digital WDR, >80dB |
| S/N Ratio | >50dB (AGC OFF) |
| White Balance | Auto / Manual |
| Gain Control | Auto / Manual |
| Noise Reduction | 2D / 3D NR |
| Lens | |
| Focal Length | 1.7mm Fisheye IR Lens |
| Infrared | |
| IR LED No. | 30pcs array LEDs |
| IR Distance | 20-m |
| Video | |
| Video Compression | H.265 / H.264 |
| Streaming Capability | Dual stream |
| Image Resolution | Main stream: 3MP (2304*1296) / 2MP (1920*1080) / 1MP (1280*720) |
| | Sub stream: 448P (800*448) / D1 (704*576) / 360P (640*360) / CIF (352*288) |
| Video Frame Rate | 3MP@30fps |
| Video Bit Rate | 0.1M ~ 8Mbps |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Network Protocols | ONVIF, P2P, CGI, HTTP, TCP/IP, IPv4, RTSP, UDP, NTP, DHCP, DNS |
| System Compatibility | Supports Onvif 2.4 Protocol |
| Smart Phone | iPhone, iPad, Android Phone |
| General | |
| Operating Temperature | -20°C-60°C |
| Operating Humidity | Less than 95%RH (No condensation) |
| Power Supply | DC12V/PoE (IEEE802.3af) |
| Housing | White color metal case, with Bracket |
| Dimensions | Φ121*85mm |